





PREMIER S9071TC - 10W

Dimmable IP64 10W LED downlight with selectable colour temperature

Application

Ideal for any retail or commercial interior space

Design Specifications

- Premium aluminium body profile, IC-4 rated
- Stylish white or silver powder coat finish
- Quality opal polycarbonate diffuser
- High efficiency SMD LED chips
- Remote constant current trailing edge dimmable LED driver, with flex and plug

Performance

Dimmable - YES Dimmer Type - Trailing edge, optional DALI





Technical Specification

Model No.	Input Voltage (V/AC)		Power (W)	Lumen (lm)	S	ССТ (К)	Beam Angle (°)		Dimmable	
S9071TC WH	240		10	800/900/9	000	3000/4000/5700	90		YES	
S9071TC SL	240		10	800/900/9	000	3000/4000/5700	90		YES	
Model No.	CRI	Body Colour		t Out nm)	D	Diameter (mm)	Dim (mm)	IPAR	T REES	
S9071TC WH	80	WHITE		92		112	57(H)	YES	YES	
S9071TC SL	80	SILVER		92		113	57(H)	YES	YES	
Model No.					VE	ET				
S9071TC WH		YES								

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the	
time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all	
IP ratings nominated for Interior products are from "below the ceiling".	

YES


S9071TC SL





Dimensions

S9071TC




Photometric Data

Photometric Data

Unit: cd C0/C180_____ C90/C270____

\$9071TC at 4000K





THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER.





For related products please scan me





NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458